

Submitted Model No.:

**Specific Features:** 

### 2 1/4" (57 mm) 2 1/4" (57 mm) 8 1/2" (216 mm) 3 15/16" 3 15/16" (100 mm) Min. 2 1/4" (57 mm) Max. 3 3/8" (86 mm) 1/2 Finished Wall -> RP72413▲ Push Button Drain RP72411▲ RP81627▲ Push Button Drain Grid Strainer Drain less overflow holes less overflow holes - 2 3/4' (41 mm) (70 mm) Dia. Dia. RP72414▲ Push Button Drain RP72412▲ Grid Strainer Drain RP81628▲ Push Button Drain with overflow holes with overflow holes with overflow holes - 2 3/4" 1 5/8" (70 mm) (41 mm) Dia. Dia.

▲ Designate proper finish suffix

# BRIZO

## **LAVATORY FAUCETS**

- Odin<sup>™</sup> Bath Collection
- Two Handle Wall-Mounted Lavatory

#### STANDARD SPECIFICATIONS:

- Max flow rate: 1.50 GPM @ 60 PSI, 5.68 L/Min @ 414 kPa
- Max flow rate (ECO models only): 1.20 GPM @ 60 PSI, 4.54 L/Min @ 414 kPa
- Three hole mount
- Ceramic cartridge
- Spout features hidden water-efficient laminar flow aerator
- Drain sold separately

#### WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



#### **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1ASME A112.18.2 / CSA B125.2 Indicates compliance to ICC/ANSI A117.1

- EPA WaterSense®
- Verified compliant with .25% weighted average Pb content regulations

Indianapolis, Indiana 46280 A Division of Masco Corporation of Indiana © 2016 Brizo Kitchen & Bath Company